

LETW-S SERIES LETW-A SERIES



LETW-S electric 2 speed straight Torque Gun



- Supply : 220-230V AC, 50/60Hz
- Preset torque and automatic shutoff when the set torque value has been reached
- High output with an accuracy of $\pm 5\%$ and consistency of $\pm 3\%$
- Single-chip intelligent torque control system with LCD display
- Has manual 2-speed gearbox, high/low speed can be selected easily
- Free connection of power handle & drive unit
- Reliable continuous working rating suitable for production assembly line, installation work and maintenance jobs
- Double insulation design for greater safety

Description	Torque (Nm)	SQD size	D (mm)	L (mm)	Speed (rpm)	Weight (kg)
LETW-08S	100-800	3/4"	88	429	20.0	7.5
LETW-12S	200-1200	1"	88	434	18.0	7.6
LETW-26S	400-2600	1"	88	455	7.0	8.2
LETW-38S	500-3800	1-1/2"	96	475	5.0	9.8
LETW-60S	1000-6000	1-1/2"	114	510	3.5	12.3
LETW-80S	1200-8000	1-1/2"	143	570	1.9	19.2
LETW-100S	1800-10000	1-1/2"	143	570	1.6	19.2
LETW-120S	2000-12000	1-1/2"	143	570	1.3	19.2

LETW-A electric 2 speed angled Torque Gun



- Supply : 220-230V AC, 50/60Hz
- Accuracy $\pm 5\%$, Consistency $\pm 3\%$
- Noise Output Level 80dB(A)
- Single-chip intelligent torque control system with LCD display
- Adjustable Twin Speed motor
- Right Angled drive head design more suitable for a limited working space area
- Main Drive head 360Deg rotation

Description	Torque (Nm)	SQD size	D (mm)	L (mm)	Speed (rpm)	Weight (kg)
LETW-08A	100-800	3/4"	88	248	20.0	8.7
LETW-12A	200-1200	1"	88	253	18.0	8.8
LETW-26A	400-2600	1"	88	274	7.0	9.4
LETW-38A	500-3800	1-1/2"	96	294	5.0	11.0
LETW-60A	1000-6000	1-1/2"	114	329	3.5	13.5
LETW-80A	1200-8000	1-1/2"	143	390	1.9	20.4
LETW-100A	1800-10000	1-1/2"	143	390	1.6	20.4
LETW-120A	2000-12000	1-1/2"	143	390	1.3	20.4